

Csavarhúzó-készlet, SOS tálcában

964/33SOS



Profilok



Termékjellemzők

- szerszámtálca mérete: 564 x 364 x 30 mm
- kompatibilis az Eurostyle, Eurovision, Euromotion, Europlus és Hercules sorozattal (előoldali fiókok)

Készlet tartalma:

- 5x lapos csavarhúzó, TBI (605TBI): 0.5x3.0x80, 0.8x4.0x100, 1.0x5.5x125, 1.2x6.5x150, 1.6x8.0x175
- 4x Phillips csavarhúzó, TBI (615TBI): PH 0x60, PH 1x80, PH 2x100, PH 3x150
- 2x lapos marokcsavarhúzó, TBI (627TBI): 1.0x5.5x25, 1.2x6.5x25
- 2x Phillips marokcsavarhúzó, TBI (626TBI): PH 1x25, PH 2x25
- 9x Torx csavarhúzó, TBI (621TBI): TX 6, TX 8, TX 10, TX 15, TX 20, TX 25, TX 27, TX 30, TX 40
- 8x dugókulcsos csavarhúzó, TBI (629TBI): 6, 7, 8, 9, 10, 11, 12, 13

940E
940EV
920PLUS

3/3

564 x 364 x 30

Termék megnevezése	SKU	Cikk	Méretek	Mennyiség
Csavarhúzó-készlet, SOS tálcaban	621392	964/33SOS	-	30
Lapos (SL) csavarhúzó TBI markolattal		605TBI	0.5 x 3.0x80, 0.8 x 4.0x100, 1.0 x 5.5x125, 1.2 x 6.5x150, 1.6 x 8.0x175	5
Phillips (PH) csavarhúzó TBI markolattal		615TBI	PH 0x60, PH 1x80, PH 2x100, PH 3x150	4
Phillips (PH) marokcsavarhúzó TBI markolattal		626TBI	PH 1x25, PH 2x25	2
Lapos (SL) marokcsavarhúzó TBI markolattal		627TBI	1.0 x 5.5x25, 1.2 x 6.5x25	2
Torx (TX) csavarhúzó TBI markolattal		621TBI	TX 6, TX 8, TX 10, TX 15, TX 20, TX 25, TX 27, TX 30, TX 40	9
Dugókulcsos csavarhúzó TBI markolattal		629TBI	6, 7, 8, 9, 10, 11, 12, 13	8
SOS tárolótálca 964/33SOS készlethez		v1964/33SOS	564x364x30	1

* A termékképek illusztrációk. minden feltüntetett méret milliméterben, a tömegek grammban. Az összes feltüntetett méret eltérhet a toleranciának megfelelően.

Safety tips



- Use a screw holding screwdriver to get screws started in awkward, hard-to-reach areas.
- Use a stubby screwdriver in close quarters where a conventional screwdriver cannot be used.
- A rounded tip should be redressed with a file; make sure edges are straight.
- Screwdrivers used in the shop are best stored in a rack. This way, the proper



- Don't use pliers on the handle of a screwdriver to get extra turning power. A wrench should only be used on the square shank or bolster of a screwdriver that is especially designed for that purpose.
- Don't expose a screwdriver blade to excessive heat as it may reduce the hardness of the blade.
- Don't use a screwdriver with a split or broken handle.

selection of the right screwdriver can be quickly made.

● Keep the screwdriver handle clean; a greasy handle is apt to cause accidents.

● A screwdriver should never be used as pry bar. If it is overstressed in this manner, the blade might break and send a particle of steel into the operator's arm or even towards his eyes.

● Don't use a regular screwdriver to check a storage battery or to determine if an electrical circuit is live.