

# Izvijač plosnati TBI

#### 602TBI



#### Profili




#### Standardi

DIN ISO 2380-1:2006 i DIN ISO 2380-2:2006

#### Atributi proizvoda

- vrh od krom-vanadij-molibdena, u cjelosti ojačan i zakaljen
- tijelo kromirano, vrh bruniran
- ručka ergonomski oblikovana
- trokomponentni materijal
- otvor u dršci za vješanje



|        | axb       | С   | L   | D   | <b>1</b> |
|--------|-----------|-----|-----|-----|----------|
| 612797 | 0.4 x 2.5 | 60  | 145 | 2.5 | 33       |
| 612798 | 0.4 x 2.5 | 75  | 160 | 2.5 | 33       |
| 611684 | 0.5 x 3.0 | 100 | 185 | 3   | 37       |

|        | axb       | C   | L   | D   | <b>1</b> |
|--------|-----------|-----|-----|-----|----------|
| 612799 | 0.5 x 3.0 | 150 | 235 | 3   | 39       |
| 612800 | 0.6 x 3.5 | 100 | 185 | 3.5 | 39       |
| 612801 | 0.8 × 4.0 | 100 | 185 | 4   | 43       |
| 611685 | 0.8 × 4.0 | 125 | 210 | 4   | 45       |
| 612802 | 0.8 × 4.0 | 150 | 235 | 4   | 48       |
| 612803 | 0.8 × 4.0 | 250 | 335 | 4   | 56       |
| 612804 | 1.0 × 5.5 | 125 | 225 | 5.5 | 75       |
| 611686 | 1.0 × 5.5 | 150 | 250 | 5.5 | 81       |
| 616843 | 1.0 x 5.5 | 280 | 380 | 5.5 | 103      |
| 612805 | 1.2 x 6.5 | 150 | 260 | 6.5 | 113      |
| 616844 | 1.2 x 6.5 | 280 | 390 | 6.5 | 145      |
| 612806 | 1.2 × 8.0 | 175 | 295 | 8   | 163      |

\* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

#### Upotreba (pictures)



### Safety tips

## $\checkmark$

• Use a screw holding screwdriver to get screws started in awkward, hard-to-reach areas.

• Use a stubby screwdriver in close quarters where a conventional screwdriver cannot be used.

• A rounded tip should be redressed with a file; make sure edges are straight.

• Screwdrivers used in the shop are best stored in a rack. This way, the proper



• Don't use pliers on the handle of a screwdriver to get extra turning power. A wrench should only be used on the square shank or bolster of a screwdriver that is especially designed for that purpose.

• Don't expose a screwdriver blade to excessive heat as it may reduce the hardness of the blade.

• Don't use a screwdriver with a split or broken handle.

selection of the right screwdriver can be quickly made.

• Keep the screwdriver handle clean; a greasy handle is apt to cause accidents.

• A screwdriver should never be used as pry bar. If it is overstressed in this manner, the blade might break and send a particle of steel into the operator's arm or even towards his eyes. • Don't use a regular screwdriver to check a storage battery or to determine if an electrical circuit is live.

#### Safety (pictures)

