

Извлекувач со два крака

680/2




Profiles



Product features

- материјал: тело од специјален флекс плус јаглороден челик, раце од специјален хром ванадиум челик
- кован, целосно појачан и кален


- завршна површина: хромирана според EN 12540, појачан среден навртувач
- краци прилагодливи во две позиции по височина
- за време на употреба краците цврсто се поставуваат близу до делот за вадење



	№	L↑	D↑			M	S	
612603	0	90	90	20	2	M 10 x 1	13	405
601762	1	130	160	30	3	M 14 x 1,5	17	915
601763	2	190	230	40	4	M20 x 2	22	2078
601764	3	250	300	60	6	M 22 x 2	24	4075

* Сликите на производите се симболични. Сите димензии се во мм, тежината е во грамови. Сите наведени димензии може да се разликуваат во ниво на толеранција

Usage (pictures)



Spare parts



— Вретено

Related products



Извлекувач со два крака на лизгање












Извлекувач со два крака на лизгање



Извлекувач со три крака

Safety (pictures)



Frequently asked questions

Can we achieve greater pulling force using a three-arm puller compared to a two-arm puller?

It depends on the dimensions. In principle, yes, because the force is distributed over several arms.

One arm broke. Do I have to replace all the arms or just the broken one?

It is necessary to change all the arms.