

Izvijač pneumatski, prihvat 1/2"

1562



Profili



Atributi proizvoda

- 7.000 o/min u slobodnom hodu
- Max. okretni moment: 813 Nm
- Max. pritisak zraka: 6, 2 bara
- Potrošnja zraka: 119 l/min
- Priključak za zrak: 1/4"
- Za vijke do M18

Prednosti:


- Kontroliran moment zatezanja
- Brzo zatezanje
- Širok spektar upotrebe





Upotreba

- Automobilska industrija
- Avionska industrija
- Poljoprivredna mehanizacija
- Teška industrija
- Veći građevinski strojevi
- Brodogradnja
- Individualna montaža

Važno!

- UVIJEK koristite Uniorove IMPACT nasadne ključeve i pribor



		L	A	B		
615321	1/2"	204	70	192	949	2800

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

Photo (pictures)



Accessories



Spojnica muška



Spojnica muška



Spojnica ženska



Spojnica ženska



Pripremna grupa 3/8"



Pripremna grupa 1/2"



Cijev spiralna za zrak

Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.