

Izvijači TBI u garnituri

607CS5TBI



Profili



Atributi proizvoda

Set sadrži:

- 3x izvijač plosnati TBI (artikal 605TBI) dim. 0.8x4.0x100, 1.0x5.5x125, 1.2x6.5x150
- 2x izvijač križni (PH) TBI (artikal 615TBI) dim. PH 1x80, PH 2x100

| Naziv proizvoda | SKU | Članak | Standardi | Količina |
|--------------------------|--------|-----------|--|----------|
| Izvijači TBI u garnituri | 611985 | 607CS5TBI | - | 5 |
| Izvijač plosnati TBI | | 605TBI | 0.8 x 4.0x100, 1.0 x 5.5x125, 1.2 x 6.5x150 | 3 |
| Izvijač križni (PH) TBI | | 615TBI | PH 1x80, PH 2x100 | 2 |

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

Safety tips



• Use a screw holding screwdriver to get screws started in awkward, hard-to-reach areas.

• Use a stubby screwdriver in close quarters where a conventional screwdriver cannot be used.

• A rounded tip should be redressed with a file; make sure edges are straight.

• Screwdrivers used in the shop are best stored in a rack. This way, the proper selection of the right screwdriver can be quickly made.

• Keep the screwdriver handle clean; a greasy handle is apt to cause accidents.

• A screwdriver should never be used as pry bar. If it is overstressed in this manner, the blade might break and send a particle of steel into the operator's arm or even towards his eyes.



• Don't use pliers on the handle of a screwdriver to get extra turning power. A wrench should only be used on the square shank or bolster of a screwdriver that is especially designed for that purpose.

• Don't expose a screwdriver blade to excessive heat as it may reduce the hardness of the blade.

• Don't use a screwdriver with a split or broken handle.

• Don't use a regular screwdriver to check a storage battery or to determine if an electrical circuit is live.

Safety (pictures)

