

Steckschlüssel 1/4 Zoll, lange Ausführung

188/2L6p



Profile







Standards

ISO 2725-1

Produkteigenschaften

- Material: Premium Flex Chrom-Vanadium-Stahl
- geschmiedet, gehärtet und vergütet
- verchromt gemäß Industriestandard ISO 1456:2009
- gefertigt laut Standard ISO 2725-1 (nur metrische Dim.)



		L	D1	D2	T	
618697	3.2	50	6	12	8	20
616881	4	50	6.8	11.9	5	20
616882	4.5	50	7.1	11.9	5	20
616883	5	50	8	11.9	5	20
616884	5.5	50	8.3	11.9	5	20
616885	6	50	9.3	11.9	8	20
616886	7	50	10.5	11.9	8	31
616887	8	50	11.9	11.9	8	71
616888	9	50	13.1	13.1	11	71
616889	10	50	14.5	14.5	11	71
616890	11	50	15.8	15.8	11	71
616891	12	50	16.8	16.8	13	71
616892	13	50	17.8	17.8	13	71
616893	14	50	19.6	19.6	16	71

* Bilder von Produkten sind Symbolfotos. Abmessungen sind in mm, Gewichte in Gramm.

Häufig gestellte Fragen

I attached the socket wrench to the pneumatic tool and the wall cracked. What could be wrong?

When working with pneumatic screwdrivers, you must use an impact socket wrench.