

Ključevi nasadni sa CR ručkom u garnituri

629CS7CR



Profili





Opis proizvoda

Sadržaj:

• 7 kom. nasadnih ključeva sa CR ručkom (art. 629CR) dim. 6, 8, 10, 12, 13, 14, 17 mm

	Naziv proizvoda	SKU	Artikal	Dimenzije	Količina
	Ključevi nasadni sa CR ručkom u garnituri	617032	629CS7CR	6 - 17	7
	Ključ nasadni sa CR ručkom		629CR	6, 8, 10, 12, 13, 14, 17	7

^{*} Fotografije proizvoda su simbolične. Sve dimenzije su u mm, a težina u gramima. Sve navedene dimenzije mogu odstupati u granicama tolerancija.

Pravilna upotreba



- Use a screw holding screwdriver to get screws started in awkward, hard-to-reach areas
- Use a stubby screwdriver in close quarters where a conventional screwdriver cannot be used
- A rounded tip should be redressed with a file; make sure edges are straight.
- Screwdrivers used in the shop are best stored in a rack. This way, the proper selection of the right screwdriver can be quickly made.
- Keep the screwdriver handle clean; a greasy handle is apt to cause accidents.
- A screwdriver should never be used as pry bar. If it is overstressed in this manner, the blade might break and send a particle of steel into the operator's arm or even towards his eyes.



- Don't use pliers on the handle of a screwdriver to get extra turning power. A wrench should only be used on the square shank or bolster of a screwdriver that is especially designed for that purpose.
- Don't expose a screwdriver blade to excessive heat as it may reduce the hardness of the blade.
- Don't use a screwdriver with a split or broken handle.
- Don't use a regular screwdriver to check a storage battery or to determine if an electrical circuit is live