

Ciocan pneumatic reversibil 1.1/2"

1596



Profile



Caracteristicile produsului

- viteza de rotatie 3000 rot/min
- moment de torsiune max. 3388 Nm
- Presiunea maxima de aer comprimat: 6, 2 Bar
- consum de aer comprimat 410 l/min
- Racord de aer 1/2"
- dimensiunea maxima a surubului (piulitei) M 45

Avantaje:

- moment de torsiune controlat
- insurubare rapida
- o diversitate de utilizari


Utilizare

- industria auto
- industria aerospatiala

- echipament agricol
- industria grea
- constructia de masini
- industria de constructii navale
- montari individuale

Important

- Folositi intotdeauna capetele chei tubulare de impact UNIOR



		B	L		
617690	1.1/2"	550	450	3388	17800

* Imaginea produsului este simbolica. Toate dimensiunile sunt exprimate în mm, greutatea în grame.

Accessories



Cuplaj, partea tata



Cuplaj, partea mama



Filtru regulator si gresor pneumatic 3/4"



Furtun pneumatic elicoidal

Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.



- Always disconnect tools not in use from the air supply.

- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.