

Mâchoire de rechange pour 722/6

722.1/7





Profils



Description produit

- Matière : acier au carbone Premium Plus
- Entièrement forgée et trempée
- Jeu de 2 pièces

	В	
623083	80	138
619020	125	378
619021	150	1030
619023	200	1365

* Les images des produits ne sont pas contractuelles. Toutes les dimensions sont en mm,

Safety tips

\checkmark

• Avoid clamping with heavy pressure on the corner of the vice jaws as it may break off a corner of a jaw.

• Replace a bent handle as soon as possible.

 ${\ensuremath{\bullet}}$ Use bolts in all of the holes in the base of the vice.

• Use lock washers under the nuts.

• When work is held in a vice for sawing, saw as close to the jaws as possible to prevent vibrations. Be careful not to cut into the jaws.

• When clamping extra long work, support the far end of work rather than putting extra pressure on the vice.

• Regularly lightly oil all moving parts.

• If the threaded part of the vice is exposed, keep it free of chips and dirt.

• Discard any vice that exhibits the slightest hairline fracture.

 Always use a vice large enough to hold the work without strain.



Don't use the jaws of a vice as an anvil.

• Never use an extension handle for extra clamping pressure.

 Never pound on the handle to tighten beyond hand pressure.

• Never try to repair a vice by welding or brazing.

Don't try to bend a heavy rod in a light vice.