

Rezervna čeljust za 722/6

722.1/7





Profili



Atributi proizvoda

- Materijal: Premium Plus ugljični čelik
- Kovana, potpuno poboljšana i ojačana
- Komplet od 2 komada

	В	
623083	80	138
619020	125	378
619021	150	1030
619023	200	1365

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

Safety tips

\checkmark

• Avoid clamping with heavy pressure on the corner of the vice jaws as it may break off a corner of a jaw.

Replace a bent handle as soon as possible.

• Use bolts in all of the holes in the base of the vice.

• Use lock washers under the nuts.

• When work is held in a vice for sawing, saw as close to the jaws as possible to prevent vibrations. Be careful not to cut into the jaws.

• When clamping extra long work, support the far end of work rather than putting extra pressure on the vice.

• Regularly lightly oil all moving parts.

• If the threaded part of the vice is exposed, keep it free of chips and dirt.

• Discard any vice that exhibits the slightest hairline fracture.

 Always use a vice large enough to hold the work without strain.

\mathbf{X}

- Don't use the jaws of a vice as an anvil.
- Never use an extension handle for extra clamping pressure.

• Never pound on the handle to tighten beyond hand pressure.

• Never try to repair a vice by welding or brazing.

Don't try to bend a heavy rod in a light vice.