

Kliješta elektrokombinirke

420/1VDEDP



Profili



Zatvori pretraživanje

DIN EN IEC 60900 (VDE 0682-201):2019-04; EN IEC 60900:2018

Atributi proizvoda


- materijal: Premium Plus ugljični čelik
- kovana, potpuno poboljšana i ojačana
- rezni rubovi induktivno kaljeni
- čeljusti polirane
- završna obrada: kromiranje po standardu ISO 1456:2009
- izrađeno po standardu EN IEC 60900

Prednosti:

• ručke izolirane sa dva izolacijska sloja u dvije boje, koje omogućavaju dodatnu sigurnost

Važno!

• ukoliko drugi sloj postane vidljiv, alat zamijenite novim.




sposobnost rezanja (10N=1kg)

			max 650 N/mm²Ø ī
619176	180	1,8	2,5

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

upotreba (pictures)



Safety tips



• Pliers should be oiled regularly. A drop of oil at the hinge will lengthen the tool life and assure easy operation.

• When cutting wire with pliers, you should always wear glasses or goggles.



• Don't use pliers for cutting hardened wire, unless specifically manufactured for this purpose.

• Don't expose pliers to excessive heat. This may ruin the tool.

Don't use pliers as a hammer.

• Don't hammer on the handles. They may crack or break.

• Don't extend the length of plier handles to secure greater leverage.

 Don't use pliers on nuts or bolts. A wrench will do a better job and with less risk of damage to the fastener.

Frequently asked questions

Are certified insulated tools made through a different procedure than noncertified insulated tools?

The tools are made according to the same procedure.

Are insulated (VDE) tools considered as personal protective equipment (PPE)?

According to EU regulations, VDE tools are not considered as PPE.

Is it possible to work with insulated pliers under electrical voltage?

Yes, but only by professionals who follow safety requirements and use additional personal protective equipment.

Are the VDE tools only being sampled in series production?

The high voltage test (at 10kV) is performed fully on each tool. Other tests are performed in accordance with the EN60900 standard.