

Cheie dinamometrica electronica

266



Profile



Caracteristicile produsului

- Atentionare atingere cuplu reglat:sonerie+12 LED
- mod de functionare:cu declansare la valoarea prestabilita
- Tipuri de unitati de masura: N-m, in-lb, ft-lb, kg-cm
- Tipul de clichet: interschimbabil
- Clichet demontabil cu 52 de dinti
- 2baterii alcaline tip AA (neincluse)
- Durata bateriei(utilizare continua):110 ore
- Durata bateriei(standby):1an
- Memoreaza pana la 250 de valori de strangere

- 10 valori de strangere prereglate
- Temperatura de lucru:-10°C ~ 60°C
- Temperatura de stocare:-20°C ~ 70°C
- Umiditate:Pana la 90% fara condens
- Test de cadere:1m
- Test de vibratii:10G
- Certificat de compatibilitate electromagnetica
- Precizie CW: +/-2%, CCW: +/-3%
- Conectare cu PC
- **Download data transfer program**
(https://www.uniortools.com/res/files/assets/Uploads/266_calibration_program.zip)

Warranty

- Garantie :10000 cicluri



627575	1/4"	1,5 - 30	390	9 x 12	1395
627576	1/2"	6,8 - 135	410	9 x 12	1619
627577	1/2"	10 - 200	545	14 x 18	2268

* Imaginea produsului este simbolica.Toate dimensiunile sunt exprimate în mm,greutatea în grame.

0 (pictures)



Photo (pictures)



Accessories



Cap cliche pentru 266



Cap de cheie reglabila pentru 266



Cap de cheie fixa pentru 266

Safety tips



- Only an authorised person in a certificated service centre can perform technical maintenance.
- Tools should always be serviced and calibrated by a certified service engineer.
- Tool should only be used for precise tightening as specified in the instruction manual.
- Check instruction manual on how to read the value scale on the tool properly.
- Stop tightening after hearing a feedback from the tool.
- Use only sockets with the same square drive.
- Always return the value on the scale back to 0 after usage and before storing.

Safety (pictures)

