

Račna pneumatska, prihvatač 3/8"

1532



Profili



Atributi proizvoda

- 200 o/min u slobodnom hodu
- Max. okretni moment 27 Nm
- Preporučeni radni tlak: 6, 2 bara
- Potrošnja zraka 113 l / min
- Priključak za zrak: 1/4"
- za vijke do M8


Prednosti:

- Uska glava račne
- Kuglični ležaj
- Gumirana ručka
- Novi sistem regulacije zraka
- Rotirajući ventil za dovod zraka: 360°
- Ispust zraka sa zadnje strane ručke
- Nizak nivo buke 79dB(A)
- Lak i kompaktna alat
- Kvalitetna proizvodnja

- Praktičan prekidač za uključivanje smjera
- Brzo i praktično podešavanje smijera rotacije

Upotreba

- Automobilska industrija
- Avionska industrija
- Poljoprivredna mehanizacija
- Teška industrija
- Veći građevinski strojevi
- Brodogradnja
- Individualna montaža
- Važno!
- Preporuča se upotreba Uniorovih IMPACT nasadnih ključeva



		L	A	B		
627566	3/8"	196	49	40,8	54	748

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

Photo (pictures)



Accessories



Spojnica muška



Spojnica muška



Spojnica ženska



Spojnica ženska



Pripremna grupa 3/8"



Pripremna grupa 1/2"



Cijev spiralna za zrak

Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.