

Račna pneumatska 1/2"

1552



Profili



Atributi proizvoda

- slobodna brzina 150 obrtaja/minut
- max. obrtni momenat 90 Nm
- preporučeni pritisak vazduha: 6, 2 bara
- potrošnja vazduha 113 l / min
- priključak za zrak: 1/4"
- za vijke do M10

Prednosti:

- uska glava
- kuglični ležaj
- gumirana ručka
- novi sistem regulacije zraka
- 360 ° dovod vazduha za okretanje
- zadnji izduvni sistem
- niski šum 79dB (A)
- mali i kompaktn alat
- kvalitetna proizvodnja


- praktičan prekidač za uključivanje
- brzo i praktično podešavanje smijera rotacije




Upotreba:

- automobilska industrija
- avionska industrija
- poljoprivredna mehanizacija
- teška industrija
- veći građevinski strojevi
- brodogradnja
- individualna montaža

Važno!

- preporuča se upotreba Uniorovih IMPACT nasadnih ključeva



		L	A	B		
627567	1/2"	256	56	47,8	90	1332

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

Upotreba (pictures)



Photo (pictures)



Accessories



Spojnica muška



Spojnica muška



Spojnica ženska



Spojnica ženska



Pripremna grupa 3/8"



Pripremna grupa 1/2"



Crijevo spiralno za zrak

Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.



- Always disconnect tools not in use from the air supply.

- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.