

Młotek pneumatyczny z zestawem dłut

1514PB










Profile

 **1 year**

Cechy produktu

- Wymiary skrzynki : 307x260x70 mm

Nazwa produktu	SKU	Artykuł	Wymiary	Ilość
Młotek pneumatyczny z zestawem dłut	619964	1514PB	-	7
Udarowy młotek pneumatyczny		1514	170	1
Dłuto płaskie		1514A1	182	1
Dłuto szpiczaste		1514A2	180	1
Dłuto do nitów i zgorzelin spawalniczych		1514A3	180	1
Dłuto do cięcia blachy		1514A4	180	1
Dłuto z końcówką V		1514A5	190	1
Dłuto z szerokim odgiętym końcem		1514A6	178	1
Plastikowa skrzynka do kluczy nasadowych		981PBM2	307x260x74	1

* Przedstawiony wygląd produktu jest orientacyjny. Wszystkie wymiary są w mm, podana waga w gramach

Wskazówki bezpieczeństwa



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.