

Reggiciclo elettrico 2.0

1693EL NOVITÀ



Profili



Attributi del prodotto

Constructed around a robust one-piece aluminum column, the Unior electric repair stand offers unparalleled stability while concealing all wires within, ensuring a clutter-free workspace for

efficient bike maintenance. It effortlessly lifts bikes up to 70kg to the desired height, ensuring optimal ergonomic conditions for every technician and every repair task. Endless height adjust makes lowering or lifting the bike with the push of a button a breeze, while automatic stopping system ensuring precise positioning. With knob adjustable travel limiters, users can customize the stand's range, while a built-in safety mechanism safeguards both technician and bicycle. With the versatile two-way control system, technician can choose between operating the stand via control panel or foot pedal, based individual preferences and needs. Additionally, an integrated adjustable LED light ensures consistent illumination, regardless of environmental lightning conditions. Built to endure, Unor Electric Repair stand is designed for longevity, requiring minimal maintenance and offers hassle free operation for years to come. Designed to be fully user serviceable, backed up with readily available spare parts and repair instructions.

Caratteristiche:

- Main electricity supply cable discreetly routed from the top, eliminating workspace obstruction.
- Fili nascosti
- Regolazione dell'altezza continua
- Operable via intuitive control panel or convenient foot pedal.
- Automatic stopping system with unloading function for enhanced safety.
- Adjustable travel limiters are controlled by knob on the panel, with memory function for added convenience.
- Display of current load ensures optimal performance.
- Two USB ports (A and C) for convenient device charging and optional Wi-Fi connectivity.
- Self-diagnosing function.
- Interfaccia della ganascia antiscivolo
- Dotato di ganascia Master shop 1693.1M
- Integrated LED light provides optimal illumination in any environment.
- Aluminum main column.
- Easily mountable directly to the floor or heavy-duty metal fixed plate.
- Ampia e robusta piastra fissa con funzione di livellamento a pavimento
- Minimal assembly required. Stand needs to be fixed to the floor or plate and control panneal attached.

Specifiche tecniche:

Load capacity: 700N (70kg)

Maximum height: 1750 mm

Power Requirements: 0,32kW

Operating Voltage: 24V DC

Input: 90V-260V; 47-63 Hz

Movement speed: 5 m/min

Valutazione IP: IP30 - solo per uso interno

Conforme CE



Nome prodotto	SKU	Articolo	Dimensioni	Quantità
Reggiciclo elettrico 2.0	629760	1693EL		2
Electric repair stand 2.0 without plate		1693EL1	90 - 260 V	1
Piastra fissa per 1693EL		1693EL.1	740x740x20	1

^{*} Le immagini dei prodotti sono puramente simboliche. Tutte le dimensioni sono in mm, peso in grammi.

Utilizzo (pictures)

















Photo (pictures)









Accessories



Piastra fissa per 1693EL



Porta laptop con braccio pieghevole per 1693EL



Vassoio portautensili con braccio pieghevole per 1693EL

Related products



Electric repair stand 2.0 without plate